

AC R134



For liquids or gas of 134A in automotive and bus air conditioning systems

TECHNICAL CHARACTERISTICS

TUBE	Special butyl compound with very low permeability
REINFORCEMENT	One high tensile steel wire braid
COVER	Black, synthetic special rubber, oil resistant, pin pricked, suitable for high temperature applications
OPERATING TEMP.	- 30°C/ + 125°C - 22°F/ + 257°F
NORMS	-

Code	Dash	Inner Diameter ID		Outside Diameter OD		Working Pressure		Burst Pressure		Theoretical Weight
		mm	inch	mm	inch	bar	psi	bar	psi	
901AC3503	3	4,8	3/16"	13,0	0,511	35	508	137	1987	0,220
901AC3504	4	6,4	1/4"	14,9	0,586	35	508	137	1987	0,280
901AC3505	5	8,0	5/16"	17,1	0,673	35	508	137	1987	0,340
901AC3506	6	10,3	13/32"	19,2	0,755	35	508	137	1987	0,400
901AC3509	8	12,7	1/2"	23,3	0,917	35	508	137	1987	0,540
901AC3510	10	16,0	5/8"	27,2	1,070	35	508	137	1987	0,680
901AC3516	16	22,2	7/8"	31,2	1,220	35	508	137	1987	0,720
901AC3520	20	28,6	1 1/8"	38,0	1,500	35	508	137	1987	0,930

