

HYDROWASH 1SN -1SC



Medium pressure hydraulic lines **88 to 225 BAR** and requires compact outer dia.
For cleaners, suitable for passage of water and detergents in aqueous solutions.

TECHNICAL
CHARACTERISTICS

TUBE	Special sunthetic rubber, resistant to hot water and detergents solution
REINFORCEMENT	One high tensile steel wire braid
COVER	Black, synthetic special rubber, pin-pricked, resistant to abrasion, oils, ozone and weathering
OPERATING TEMP.	Continuous: -40°C to +120°C
NORMS	-

1 SN Code	Dash	Inner Diameter ID		Outside Diameter OD		Working Pressure		Burst Pressure		Theoretical Weight Kg/m
		mm	inch	mm	inch	bar	psi	bar	psi	
901W104	4	6,4	1/4"	13,4	0,527	230	3300	900	13050	0,220
901W105	5	7,9	5/16"	15,0	0,590	230	3300	860	12470	0,270
901W106	6	9,5	3/8"	17,4	0,685	210	3000	720	10440	0,350

1 SC Code	Dash	Inner Diameter ID		Outside Diameter OD		Working Pressure		Burst Pressure		Theoretical Weight Kg/m
		mm	inch	mm	inch	bar	psi	bar	psi	
901WR104	4	6,4	1/4"	12,4	0,488	230	3300	900	13050	0,184
901WR105	5	7,9	5/16"	14,1	0,555	230	3300	860	12470	0,216
901WR106	6	9,5	3/8"	16,1	0,633	210	3000	720	10440	0,281

